

(Following Paper ID and Roll No. to be filled in your Answer Book)

Paper ID :140524

Roll No.

--	--	--	--	--	--	--	--	--	--

B.Tech.

(SEM. V) THEORY EXAM. 2015-16

HEAT & MASS TRANSFER (EME-504)

[Time:3 hours]

[MaximumMarks:100]

SECTION-A

Q.1 Attempt all parts. All part carry equal marks. Write answer of each part in short. (2x10=20)

- (a) How do thermal conductivities of gases and non-metals vary with temperature?
- (b) Derive the expression for logarithmic mean area for the hollow cylinder.
- (c) Discuss the physical significance of effectiveness.
- (d) What do you understand by lumped system, explain it with suitable example?
- (e) Thermal time constant and response of temperature measuring instrument.

- (f) Explain one-seventh power law over a flat plate.
- (g) Write down the assumptions which are made for the analysis of heat flow through the fin.
- (h) Discuss the following.
- (i) Nusselt number and its physical significance.
- (ii) Grashoff's number and its physical significance.
- (i) Write short note on fouling or scaling.
- (j) A gray diffuse opaque surface ($\alpha = 0.8$) is at 100°C and receives an radiation 1000 W/m^2 . If the surface area is 0.1 m^2 . Calculate:
- (i) Radiosity of the surface.
- (ii) Net radiation heat transfer rate from the surface.
- (iii) Calculate above quantities if the surface is black.

SECTION-B

Note: Attempt any five questions from this section.

(10x5=50)

- Q.2. What do you mean by modes of heat transfer? Describe its governing laws in detail. Also describe the case of combined heat transfer by required expression.

- Q.3 What is thermometer well, describe it with neat sketch and prove that the temperature measured by a thermometer well is not a true temperature of fluid.
- Q.4 What do you mean by radiation shield? Derive the expression of net heat transfer rate for a system of two parallel plates separated by n -shields of emissivity's $\epsilon_1, \epsilon_2, \epsilon_3, \dots, \epsilon_n$.
- Q.5 Give the detail classification of heat exchanger. Write down the governing parameters for analysis of heat exchanger. Also explain the compact heat exchanger with neat sketch.
- Q.6 Explain the following in details.
- (i.) Intensity of radiation.
- (ii.) Shape factor algebra, facts and properties.
- Q.7 Steam in the condenser of a power plant is to be condensed at a temperature of 30°C with cooling water from a nearby lake, which enters the tubes of the condenser at 14°C and leaves at 22°C . The surface area of the tubes is 45 m^2 and the overall heat transfer coefficient is $2100 \text{ W/m}^2^\circ\text{C}$. Determine the mass flow rate of the cooling water needed and the rate of condensation of the steam in the condenser. Heat of vaporization of water at 30°C 2431 kJ/kg . and $C_p = 4184 \text{ J/kg}^\circ\text{C}$.

- 8 Determine the coefficient of heat transfer by free convection and maximum current density for a nichrom wire 0.5 mm in diameter. The surface of the wire is maintained at 300 °C. The wire is exposed to still air at 20 °C and resistance per meter length of the wire is $6 \Omega/\text{m}$. Use relation: $Nu = 1.18 (Gr Pr)^{1/8}$.

Use properties of air at 160 °C-

$$K_f = 0.0361 \text{ W/m K}, \quad \nu = 30.35 \times 10^{-6} \text{ m}^2/\text{s}, \quad Pr = 0.687$$

- 9 Consider a diffuse circular disk of diameter D and area A_j and a plane diffuse surface of area $A_i \ll A_j$. The surfaces are parallel and A_i is located at a distance L from the center of A_j .

Obtain the following expression for the view factor

$$F_{ij} = \frac{D^2}{D^2 + L^2}$$

SECTION-C

Attempt any two questions from this section. (15x2=30)

- Q.10 (a) Derive the general heat conduction equation in Cartesian co-ordinate for homogeneous and isotropic material.

- (b) A wall is constructed of several layers. The first layer consists of bricks ($k=0.66 \text{ W/m K}$), 25 cm thick, the second layer is 2.5 cm thick mortar ($k=0.7 \text{ W/m K}$), the third layer 10 cm thick limestone ($k=0.66 \text{ W/m K}$) and outer layer of 1.25 cm thick plaster ($k=0.7 \text{ W/m K}$). The heat transfer coefficients on interior and exterior of the wall are 5.8 $\text{W/m}^2\text{K}$ and 11.6 $\text{W/m}^2\text{K}$, respectively. Find:

- (i) Overall heat transfer coefficient, (ii) Overall thermal resistance per m^2 , (iii) Rate of heat transfer per m^2 , if the interior of the room is at 26 °C while outer air is at 7 °C, (iv) Temperature at the junction between mortar and limestone.

- Q.11 (a) Write down the name of some common types of fin with neat sketch. Also derive the expression for heat dissipation through rectangular fin which is infinitely long.

- (b) A Copper pipe carrying refrigerant at -20 °C is 10 mm in outer diameter and is exposed to ambient at 25 °C with convective coefficient of 50 $\text{W/m}^2\text{K}$. It is proposed to apply the insulation of material having thermal conductivity of 0.5 W/mK . Determine the thickness beyond which the heat gain will be reduced. Calculate the heat losses for 2.5 mm, 7.5 mm, and 15 mm thick layer of insulation over 1 m length.

Q.12 (a) Describe the boundary layer thickness and derive the expression for energy thickness.

(b) An iron sphere of diameter 5 cm is initially at a uniform temperature of 225°C . It is suddenly exposed to an ambient at 25°C with convection coefficient of $500 \text{ W/m}^2\text{k}$.

(i) Calculate the centre temperature 2 minute after the start of exposure.

(ii) Calculate the temperature at the depth of 1 cm from the surface after 2 minute of exposure.

(iii) Calculate the energy removed from the sphere during this period. Take thermo-physical properties of iron plate:

$$k=60 \text{ W/mK}, \rho=7850\text{kg/m}^3, C=460 \text{ J/Kg}, \\ \alpha = 1.6 \times 10^{-5} \text{ m}^2/\text{s}$$

—x—